


ARKE



DRIVER OPTIONS	CCT OPTIONS
OF On/Off	2700K Warm white
	3000K Warm white
	4000K Neutral white
	5000K Cool white

COD.	POWER	LUMEN	B.ANGLE	SIZE (mm)
41230008	8W	1271 lm	Asymmetric	120 x 120 x 80 h
41231016	16W	2384 lm	Asymmetric	160 x 160 x 100 h


OPTIONAL

FINISHING: Black

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Arke, è una luce da parete che offre un angolo di fascio asimmetrico e un design geometrico che conferisce un aspetto sofisticato e contemporaneo a qualsiasi ambiente esterno. Le sue linee pulite e la forma audace creano un effetto luminoso dinamico, bilanciando perfettamente stile e prestazioni elevate, massimizzando al contempo l'efficienza energetica.

Alloggiamento: Alluminio pressofuso verniciato a polvere

Riflettore: Alluminio anodizzato

Diffusore: Vetro temperato trasparente

LED: Tecnologia LED avanzata che riduce il consumo energetico (L80/B10/F10), con una durata di 50.000 ore, progettato per funzionare efficacemente in temperature da -21°C a 56°C.

The Arke wall light boasts an asymmetrical beam angle and a geometric design that brings a sophisticated, contemporary look to any outdoor setting. Its clean lines and bold form create a dynamic light effect, perfectly balancing style with high performance, all while maximizing energy efficiency.

Housing: Die-cast aluminum powder-coated

Reflector: Anodized aluminum

Diffuser: Tempered clear glass

LED: Advanced LED technology reduces energy consumption (L80/B10/F10), with a 50,000-hour lifespan, designed to operate effectively in temperatures ranging from -21°C to 56°C.

Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

