


ARTEVO



DRIVER OPTIONS	CCT OPTIONS
OF On/Off	2700K Warm white 3000K Warm white 4000K Neutral white 5000K Cool white 6000K Cool white 6500K Cool white
OPTIONAL	

FINISHING: White, Black

COD.	POWER	LUMEN	B. ANGLE	HOLE (mm)	DIM./SIZE (mm)
41301002	2W	180 lm	40°	Ø90	Ø110 x 34

BEAM ANGLE



Artevo è una luce da lettura rotonda che unisce armoniosamente un fascio di luce focalizzato a un anello luminoso distintivo, offrendo sia illuminazione diretta che diffusa. Progettato per garantire funzionalità moderna, è dotato di un caricatore USB integrato, rendendolo una soluzione pratica ed elegante per ambienti contemporanei.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Tecnologia LED a basso consumo con classificazione L80/B10/F10, durata di 50.000 ore e funzionamento stabile con temperature da -21°C a 56°C

Artevo is a round reading light that seamlessly combines a focused spotlight with a distinctive halo ring, delivering both precision and ambient illumination. Designed for modern functionality, it features an integrated USB charger, making it a convenient and stylish addition to contemporary spaces.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Energy-efficient LED technology with an L80/B10/F10 rating, ensuring a 50,000-hour lifespan and reliable performance in temperatures from -21°C to 56°C

COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

