

BELLA



DRIVER OPTIONS

OF On/Off

CCT OPTIONS

2700K Warm white
 3000K Warm white
 4000K Neutral white
 5000K Cool white
 6000K Cool white
 6500K Cool white

OPTIONAL

FINISHING: White, Black

COD.	POWER	LUMEN	B.ANGLE	HOLE (mm)	DIM./SIZE (mm)
41414003	3W	140 lm	Flush	40 x 166	50 x 48 x 177 h

BEAM ANGLE



LIGHT DISTRIBUTION

h(m)	E(lx)	ø(m)
1	8.825	ø0.76
2	2.206	ø1.52
3	0.980	ø2.29
4	0.551	ø3.05
5	0.353	ø3.81

COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Italy Bella, con la sua forma ultrasottile, è una luce da parete sofisticata, progettata per un'illuminazione discreta ma efficace. Il suo profilo elegante e minimalista si integra armoniosamente negli interni moderni, offrendo eleganza e un tocco di lusso. Pensata per combinare estetica e funzionalità, Bella arricchisce ogni ambiente con una luce morbida e ben distribuita.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Tecnologia LED a basso consumo con classificazione L80/B10/F10, durata di 50.000 ore e funzionamento stabile con temperature da -21°C a 56°C

UK Bella, with its ultra-slim shape, is a refined step light designed for subtle yet effective illumination. Its sleek, minimalist profile blends effortlessly into modern interiors, offering elegance and a hint of luxury. Designed for both aesthetics and functionality, Bella enhances any space with its soft, well-distributed lighting.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Energy-efficient LED technology with an L80/B10/F10 rating, delivering a 50,000-hour lifespan and stable operation in temperatures from -21°C to 56°C

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

