


BINOCOLO




RECESSED / A INCASSO

DRIVER OPTIONS	CCT OPTIONS
OF On/Off	2700K Warm white
	3000K Warm white
	4000K Neutral white
	5000K Cool white
	6000K Cool white
	6500K Cool white
OPTIONAL	

FINISHING: White, Black

COD.	POWER	LUMEN	B.ANGLE	HOLE (mm)	DIM./SIZE (mm)
40133007	7W	385 lm	15°/25°/36°/55°	Ø66	Ø75 x 45 h

BEAM ANGLE



LIGHT DISTRIBUTION

h(m)	E(lx)	Ø(m)
1	2618	Ø0.33
2	654.4	Ø0.66
3	290.9	Ø0.99
4	163.6	Ø1.32
5	104.7	Ø1.65

COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Binocolo è un faretto inclinabile a bassa abbagliamento progettato per l'uso indoor, con un design regolabile che lo rende ideale per un'illuminazione mirata. La sua funzionalità versatile consente un controllo preciso della luce in una varietà di ambienti.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Riduce il consumo energetico con una valutazione L80/B10/F10, garantendo una durata di 50.000 ore e prestazioni affidabili in un intervallo di temperature da -21°C a 56°C.

Binocolo is a low-glare tilt spotlight designed for indoor use, offering an adjustable design that makes it perfect for focused illumination. Its versatile functionality allows for precise lighting control in a variety of settings.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Reduces energy consumption with an L80/B10/F10 rating, providing a 50,000-hour lifespan and reliable performance in temperatures ranging from -21°C to 56°C.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

