


CASA



DRIVER OPTIONS

OF On/Off
PH Phase dimming

CCT OPTIONS

2700K Warm white
3000K Warm white
4000K Neutral white
5000K Cool white
6000K Cool white
6500K Cool white

OPTIONAL

FINISHING: White, Black



COD.	POWER	LUMEN	B.ANGLE	DIM./SIZE (mm)
41284005	5.4W	523 lm	40°	Ø70 x 91.5 x 95 h

BEAM ANGLE



Italy Casa Wall Surface Light è progettata per valorizzare gli spazi esterni, combinando durata e stile. Realizzata in alluminio pressofuso, garantisce sia prestazioni durature che un aspetto moderno e raffinato, ideale per ogni ambiente esterno.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Progettato per ridurre il consumo energetico con una classificazione L80/B10/F10, garantendo una durata di 50.000 ore e funzionando a temperature comprese tra -21°C e 56°C.

UK Casa Wall Surface Light is designed to elevate outdoor spaces with a combination of durability and style. Crafted from die-cast aluminum, it ensures both long-lasting performance and a sleek, modern appearance, perfect for enhancing any exterior.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Designed to reduce energy consumption with an L80/B10/F10 rating, providing a 50,000-hour lifespan and capable of operating in temperatures from -21°C to 56°C.

LIGHT DISTRIBUTION

h(m)	E(lx)	Ø(m)
1	948.7	Ø0.70
2	237.2	Ø1.39
3	105.4	Ø2.09
4	59.30	Ø2.78
5	37.95	Ø3.48

COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

