

CHROMA COMMAND DMX ELITE

 Introducing the ChromaCommand DMX Elite, a cutting-edge controller designed to elevate your lighting experience with a host of advanced features:

1. Efficient Data Storage: The ChromaCommand DMX Elite adopts a 4GB TF card for data storage, accommodating a variety of programs with ease.

2. Versatile Program Playback: The system supports automatic program playback, timing functions, and preset effects for festivals, providing flexibility for diverse lighting scenarios.

3. Innovative Touch Screen Design: The controller features a touch screen with a sinking design, effectively protecting it and minimizing the risk of accidental touches.

4. Comprehensive Program Control: The ChromaCommand DMX Elite allows for program segment selection, overall brightness adjustment, white balance adjustment, play speed adjustment, and more, ensuring precise control over your lighting setup.

5. Flexible Signal Integration: By combining the DMX512 signal with synchronous serial shift data signal (not simultaneously output), the controller offers flexibility to meet various customer requirements.

6. Synchronization Options: While not supporting online control, the ChromaCommand DMX Elite provides multiple synchronization options such as GFFIS synchronization, AC synchronization, synchronous line synchronization, or no synchronization.

Elevate your lighting control with the ChromaCommand DMX Elite, a versatile and innovative solution designed to meet the dynamic demands of diverse lighting environments.

 Presentiamo il ChromaCommand DMX Elite un controller all'avanguardia progettato per elevare la tua esperienza illuminotecnica con una serie di funzioni avanzate:

1. Efficiente Archiviazione Dati: Il ChromaCommand DMX Elite adotta una scheda TF da 4GB per l'archiviazione dati, consentendo di gestire facilmente una varietà di programmi.

2. Riproduzione Versatile dei Programmi: Il sistema supporta la riproduzione automatica dei programmi, funzioni di temporizzazione ed effetti preimpostati per festival, offrendo flessibilità per diverse scenografie luminose.

3. Design Innovativo del Touch Screen: Il controller presenta un touch screen con un design affondato, proteggendolo efficacemente e riducendo al minimo il rischio di toccate accidentali.

4. Controllo Completo dei Programmi: Il ChromaCommand DMX Elite consente la selezione del segmento del programma, la regolazione complessiva della luminosità, la regolazione del bilanciamento del bianco, la regolazione della velocità di riproduzione e altro ancora, garantendo un controllo preciso della tua configurazione luminosa.

5. Integrazione Flessibile del Segnale: Combinando il segnale DMX512 con il segnale di dati a scorrimento seriale sincrono (non in uscita contemporanea), il controller offre flessibilità per soddisfare varie esigenze dei clienti.



COD.	42503015
SIZE (mm)	153 x 90 x 31 h
DRIVER	AC 9V; DC 7.5V - 24V; DC 5V
POWER	15W
OUTPUT WAYS	2 ports for DMX512; 2 ports for SPI (not to be selected at once)
CONTROL PIXEL	340 px for DMX; 1024 px for SPI; support extension
CONTROL EFFECT	words, animation, images, video
TF CARD VOLUME	4 GB
COMM. INTERFACE	without cascade and communication interface
PROGRAMS	80
SPEED GRADE	100
BRIGHTNESS ADJ. GRADE	100
PROTECTION GRADE	IP20
ADDRESSING METHOD	auto addressing (each luminaire can be addressed and located in sequence)
WORKING TEMP.	-40°C ~50°C
FIXED HOLE GAP (mm)	-
APPLICATION	outdoor/indoor led lighting project

6. Opzioni di Sincronizzazione: Sebbene non supporti il controllo online, il ChromaCommand DMX Elite fornisce diverse opzioni di sincronizzazione come la sincronizzazione GFFIS, la sincronizzazione AC, la sincronizzazione della linea sincrona o nessuna sincronizzazione.



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.