


CORIA



SURFACE / SUPERFICIE

DRIVER OPTIONS

OF On/Off


CCT OPTIONS

3000K Warm white
4000K Neutral white


OPTIONAL

REFLECTOR: White
Black
Gold
Silver

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



COD.	POWER	LUMEN	B.ANGLE	SIZE (mm)
40221010	10W	780 lm	15°/24°/38°/55°	Ø 75 x 90 h
40221015	15W	1150 lm	15°/24°/38°/55°	Ø 75 x 90 h
40222020	20W	1560 lm	15°/24°/38°/55°	Ø 91 x 112 h
40223025	25W	1880 lm	15°/24°/38°/55°	Ø 128 x 137 h
40223030	30W	2285 lm	15°/24°/38°/55°	Ø 128 x 137 h

Il design minimalista è l'eterna ricerca del designer. La varietà di riflettori per il controllo della luce offre ai designer immaginazione e spazio per disegnare con la luce. La combinazione multi-ottica antiriflesso crea un ambiente luminoso confortevole.

Alloggiamento: alluminio pressofuso

Riflettore: alluminio anodizzato con opzioni di colore

Diffusore: lente in vetro temperato

LED: risparmio energetico L80/B10/F10 - durata 50.000 h - temperatura di lavoro da -21°C a 56°

Minimalist design is the eternal pursuit of design. Variety of light control cups gives designers imagination and space for designing with light. Multi-optical anti-glare combination creates a comfortable light environment.

Housing: die cast aluminium

Reflector: anodized aluminium with color options

Diffuser: tempered glass lens

LED: reduce energy consumption with L80/B10/F10 - 50.000 hrs lifetime working under temp (-21°C to 56°C)

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

