


CRONO



DRIVER OPTIONS	CCT OPTIONS	COD.	POWER	LUMEN	B. ANGLE	HOLE (mm)	DIM./SIZE (mm)
OF On/Off	2700K Warm white 3000K Warm white 4000K Neutral white 5000K Cool white 6000K Cool white 6500K Cool white	41421002	2W	159 lm	40°	Ø80	Ø105 x 60 h
OPTIONAL							
FINISHING: White, Black							

BEAM ANGLE



Italy Crono è una lampada da incasso a parete dal design discreto ed elegante, perfetta per integrarsi armoniosamente in qualsiasi ambiente. Il meccanismo innovativo a scorrimento permette di accendere la luce estraendola e spegnerla semplicemente spingendola indietro, garantendo praticità e funzionalità.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Tecnologia LED a basso consumo con classificazione L80/B10/F10, durata di 50.000 ore e funzionamento affidabile con temperature da -21°C a 56°

UK Crono is a round wall-recessed light designed for seamless integration into any environment. Its discreet and stylish design makes it an ideal choice for modern spaces. Featuring an innovative slide-out mechanism, it effortlessly turns "on" by sliding out and "off" by pushing back, offering both convenience and functionality.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Energy-efficient LED technology with an L80/B10/F10 rating, offering a 50,000-hour lifespan and reliable operation in temperatures ranging from -21°C to 56°C

COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

