


DELIA ADJ



VOLTAGE

AC100-240V (6W)
AC220-240V (11W)

DRIVER OPTIONS

OF On/Off


CCT OPTIONS

2700K Warm white
3000K Warm white
4000K Neutral white
5000K Cool white


OPTIONAL

FINISHING: Silver

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



COD.	POWER	LUMEN	B.ANGLE	HOLE (mm)	SIZE (mm)
41110006	6W	487 lm	15°/24°/36°/50°	Ø 118	Ø 116 x 163 h
41111011	11W	931 lm	15°/24°/36°/50°	Ø 118	Ø 116 x 163 h

IT Delia Adj è progettata per offrire illuminazione efficiente e costante agli spazi esterni. La sua costruzione solida è pensata per resistere alle condizioni più difficili, garantendo prestazioni affidabili tutto l'anno. Dotato di tecnologia LED di alta qualità, garantisce risparmi energetici senza compromettere l'illuminazione. Ideale per l'installazione in terreno o ghiaia, il Delia Adj fonde senza sforzo durabilità e estetica moderna, rendendolo una scelta perfetta per migliorare il design del tuo spazio esterno.

Alloggiamento: Corpo in alluminio pressofuso con copertura in acciaio inossidabile

Diffusore: Vetro temperato trasparente

LED: Tecnologia LED all'avanguardia (L80/B10/F10) con una durata di 50.000 ore, che offre prestazioni ottimali a temperature comprese tra -21°C e 56°C.

UK Delia Adj is a compact powerhouse, built to deliver efficient and consistent lighting for your outdoor spaces. Its solid construction is designed to withstand the toughest conditions, providing reliable performance year-round. Featuring high-quality LED technology, it ensures energy savings without compromising on illumination. Ideal for installation in soil or gravel, the Delia Adj effortlessly blends durability with modern aesthetics, making it an excellent choice for enhancing your outdoor design.

Housing: Sturdy die-cast aluminum body with a durable stainless steel cover

Diffuser: Transparent tempered glass

LED: Cutting-edge LED (L80/B10/F10) with a lifespan of 50,000 hours, performing efficiently in temperatures ranging from -21°C to 56°C.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.



Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.