



DOMEA QUADRO




RECESSED / A INCASSO


DRIVER OPTIONS	CCT OPTIONS
OF On/Off	3000K Warm white
DL DALI	4000K Neutral white
IV 1/10V dimming	
TR Triac	
PH Phase dimming	
OPTIONAL	

REFLECTOR: Chrome black
Shining silver
Shining gold
Matt white
Matt black

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



COD.	POWER	LUMEN	B.ANGLE	HOLE (mm)	SIZE (mm)
40020005	5W	378 lm	15°/24°/38°/55°	55 x 55	62 x 62 x 77 h
40020007	7W	488 lm	15°/24°/38°/55°	55 x 55	62 x 62 x 77 h
40021010	10W	923 lm	15°/24°/38°/55°	75 x 75	85 x 85 x 92 h
40021015	15W	1241 lm	15°/24°/38°/55°	75 x 75	85 x 85 x 92 h
40022020	20W	1630 lm	15°/24°/38°/55°	95 x 95	104 x 104 x 117
40022025	25W	1920 lm	15°/24°/38°/55°	95 x 95	104 x 104 x 117

Italy Domea Quadro è una sofisticata aggiunta alla famiglia Domea di faretti architettonici modulari, dotato di un'unica sorgente luminosa e una vasta gamma di accessori. Questo modello presenta una cornice quadrata e un'installazione a incasso per un aspetto pulito e minimalista. Il riflettore anti-abbagliamento assicura un aspetto discreto in tutte le versioni, migliorando il comfort visivo riducendo l'abbagliamento.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato con opzioni di personalizzazione del colore e della forma

Diffusore: Lente in vetro temperato o lente in PMMA

LED: Riduce il consumo energetico con L80/B10/ F10, offrendo una durata di 50.000 ore e prestazioni efficienti in un intervallo di temperature da -20°C a 50°C.

UK Domea Quadro is an elegant addition to the Domea family of modular architectural spotlights, featuring a single light engine and a wide range of accessories. This model showcases a square trim and recessed installation for a clean, minimalistic appearance. The anti-glare reflector guarantees a discreet look across all versions, enhancing visual comfort by reducing glare.

Housing: Die-cast aluminum

Reflector: Anodized aluminum with color and shape customization options

Diffuser: Tempered glass lens or PMMA lens

LED: Minimizes energy consumption with L80/B10/ F10, providing a 50,000-hour lifespan and efficient performance within a temperature range of -20°C to 50°C.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

