

DROP




RECESSED / A INCASSO

DRIVER OPTIONS	CCT OPTIONS
OF On/Off	2700K Warm white
	3000K Warm white
	4000K Neutral white
	5000K Cool white
	6000K Cool white
	6500K Cool white
OPTIONAL	

FINISHING: White, Black

COD.	POWER	LUMEN	B.ANGLE	HOLE (mm)	DIM./SIZE (mm)
42928003	3W	62 lm	20°/30°/40°	Ø34	Ø30 x 43 h

BEAM ANGLE



LIGHT DISTRIBUTION

h(m)	E(lx)	Ø(m)
1	276.0	Ø0.61
2	69.00	Ø1.22
3	30.67	Ø1.82
4	17.25	Ø2.43
5	11.04	Ø3.04

COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Drop è un faretto con Mini Snoot e design semi-pendente, che offre un aspetto elegante e moderno. Il suo design garantisce un'illuminazione mirata con un aspetto raffinato, ideale per evidenziare aree specifiche con stile.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Riduce il consumo energetico con L80/B10/F10, garantendo una durata di 50.000 ore e prestazioni affidabili in un intervallo di temperature da -21°C a 56°C.

Drop is a spotlight featuring a Mini Snoot with a semi-pendant design, offering a sleek and modern look. Its design ensures focused illumination with an elegant appearance, perfect for highlighting specific areas with style.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Reduces energy consumption with L80/B10/F10, offering a 50,000-hour lifespan and reliable performance in temperatures ranging from -21°C to 56°C.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

