


FARES



RECESSED / A INCASSO

DRIVER OPTIONS

OF On/Off
DL DALI
IV 1/10V dimming
TR Triac
PH Phase dimming


CCT OPTIONS

3000K Warm white
4000K Neutral white


OPTIONAL

FINISHING: White

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



COD.	POWER	LUMEN	B.ANGLE	HOLE (mm)	SIZE (mm)
40040008	8W	726 lm	15°/24°/36°/45°/55°	Ø80	Ø90 x 105 h
40040012	12W	1061 lm	15°/24°/36°/45°/55°	Ø80	Ø90 x 105 h
40040015	15W	1543 lm	15°/24°/36°/45°/55°	Ø80	Ø90 x 105 h
40040020	20W	1188 lm	15°/24°/36°/55°	Ø105	Ø115 x 113 h
40040025	25W	1353 lm	15°/24°/36°/55°	Ø105	Ø115 x 113 h

Italy Fares è una serie versatile di faretti architettonici, progettata per integrarsi perfettamente in qualsiasi ambiente. Dotato di un cono anti-abbagliamento nero, questa caratteristica garantisce un aspetto elegante e discreto, riducendo al contempo l'abbagliamento e offrendo un comfort visivo superiore. La distribuzione uniforme della luce rende Fares ideale per aree che richiedono un'illuminazione costante e bilanciata. Con un angolo di inclinazione fino a 30°, può essere installato su soffitti inclinati, offrendo maggiore flessibilità di posizionamento.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

Diffusore: Lente in vetro temperato o lente in PMMA

LED: Progettato per ridurre il consumo energetico (L80/B10/F10) con una durata di 50.000 ore, funziona in modo efficiente a temperature comprese tra -20°C e 50°C.

UK Fares is a versatile series of architectural spotlights, designed to blend seamlessly into any environment. Equipped with a black anti-glare cone, this feature ensures a sleek and understated look while reducing glare, offering superior visual comfort. The uniform light distribution makes the Fares ideal for areas where consistent and balanced illumination is needed. With a pivot angle of up to 30°, it can be installed on sloped ceilings for added flexibility in positioning.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

Diffuser: Tempered glass lens or PMMA lens

LED: Engineered to reduce energy consumption (L80/B10/F10) with a long-lasting 50,000-hour lifespan, it operates efficiently in temperatures from -20°C to 50°C.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

