


FARO



VOLTAGE

AC180-264V (12W)
AC220-240V (22W)

DRIVER OPTIONS

OF On/Off
DL DALI
IV 1/10V dimming
TR Triac

CCT OPTIONS

2700K Warm white
3000K Warm white
4000K Neutral white
6000K Cool white

OPTIONAL

FINISHING: Black




COD.	POWER	LUMEN	B.ANGLE	SIZE (mm)
41301012	12W	155 lm	Asymmetric	Ø95 × 500 h
41302012	12W	155 lm	Asymmetric	Ø95 × 800 h
41303022	22W	364 lm	Asymmetric	Ø160 × 500 h
41304022	22W	364 lm	Asymmetric	Ø160 × 800 h

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



■ Faro presenta un design semplice e raffinato, con la possibilità di scegliere tra un diffusore opalino o trasparente per ottenere un effetto luminoso più brillante o più morbido. Entrambe le versioni sono dotate di un chip LED ad alta efficienza che assicura un eccellente flusso luminoso, offrendo un fascio di luce piacevole, uniforme e confortevole. Perfetto per piccole strade, piazze, giardini e parchi, Faro è disponibile in diverse altezze.

Alloggiamento: Alluminio pressofuso verniciato a polvere con una selezione di colori RAL.

Diffusore: Diffusore in policarbonato PMMA, progettato appositamente per LED.

LED: Riduce il consumo energetico con L80/B10/F10, garantendo una durata di 50.000 ore di funzionamento, e operando in modo efficace in temperatura da -21°C a 56°C.

■ Faro offers a timeless, simple design with a choice of opal or clear diffusers, allowing you to adjust the light effect from brighter to softer. Both versions are equipped with a high-efficiency LED chip that ensures excellent luminous flux, providing a pleasant, uniform, and comfortable light beam. Ideal for small streets, squares, gardens, and parks, Faro is available in various height options.

Housing: Die-cast aluminum, powder-coated with a range of RAL colors.

Diffuser: PMMA polycarbonate diffuser, designed specifically for LED.

LED: Reduces energy consumption with L80/B10/F10, offering a 50,000-hour lifespan, and operates effectively in temperatures from -21°C to 56°C.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

