


GIUFLAT



Design ottico asimmetrico
Asymmetric optic design



DRIVER OPTIONS

OF On/Off

CCT OPTIONS

2700K Warm white
3000K Warm white
4000K Neutral white
5000K Cool white
6000K Cool white
6500K Cool white


OPTIONAL

FINISHING: Bronze

COD.	POWER	LUMEN	SIZE (mm)
31205040	40W	5200 lm	296 x 150 x 223
31205070	70W	9100 lm	296 x 150 x 223

BEAM ANGLE

LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



LED wall disegnato per aree come strutture ed edifici, cortili e superfici murali. Facile installazione. Design a ottiche asimmetriche, ottimizza la luce nell'area sottostante il muro. Controllo della luce intelligente (daylight). Humanized Foam Design: previene dalle infiltrazioni d'acqua all'interno del driver.

Alloggiamento: alluminio pressofuso verniciato a polvere, color bronzo

Diffusore: policarbonato specifico per il LED

LED: risparmio energetico L80/B10/F10 - durata 50.000 h - temperature di lavoro da -21°C a 56°

LED wall pack designed for areas like outdoor lighting and courtyard illumination. Easy Installation. Powder Coating, Sand Textured & Bronze Coloured Surface. Asymmetric Optics Design. Intelligent daylight control. Humanized Foam Design: prevent water from flowing into driver compartment.

Housing: die cast aluminium powder coated bronze colored

Diffuser: PMMA PC diffuser specially for LED

LED: reducy energy consumption with L80/B10/F10 - 50.000 hrs lifetime working under temp (-21°C to 56°C)

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.



Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.