


GLOBO



DRIVER OPTIONS

OF On/Off
DL DALI
IV 1/10V dimming

OPTIONAL

FINISHING: White

CCT OPTIONS


2700K Warm white
3000K Warm white
4000K Neutral white
5000K Cool white
6000K Cool white
6500K Cool white

COD.	POWER	LUMEN	B.ANGLE	SIZE (mm)
31523030	30W	3300 lm	120°	295 x 595 x 10 h
31523035	35W	3850 lm	120°	295 x 1195 x 10 h
31523036	36W	3960 lm	120°	595 x 595 x 10 h
31523039	39.5W	4400 lm	120°	595 x 595 x 10 h
31523044	44W	4840 lm	120°	595 x 595 x 10 h
31523048	48W	5280 lm	120°	595 x 595 x 10 h

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Globo è un elemento modulare per controsoffitto, particolarmente indicato per illuminare uffici ed ambienti pubblici. La sorgente LED fornisce eccellenti performance luminose; la luce è gestita attraverso un diffusore in PMMA opalino che distribuisce la luce in modo uniforme.

Alloggiamento: cornice in alluminio estruso con finitura alluminio o verniciata a polvere (RAL opzionale). Kit di montaggio per incasso, superficie o sospensione

Diffusore: foglio diffusore in PMMA opalino a basso UGR

LED: risparmio energetico L80/B10/F10 - durata 50.000 h - temperatura di lavoro da -21°C a 56°

Globo is a modular lighting fixture for false ceilings, particularly suitable to illuminate offices and public spaces. The LED source ensures excellent light performance; light is managed through an opaline PMMA diffuser for light distribution and control.

Housing: extruded aluminium frame with aluminium finish or powder coated with different RAL color option. Equip with kit to be suspended or recessed or pushing type

Diffuser: PMMA opal low UGR diffusing sheet

LED: reduce energy consumption with L80/B10/F10 - 50.000 hrs lifetime working under temp (-21°C to 56°C)

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

