


IRINA



VOLTAGE

DC24V

DRIVER OPTIONS

OF On/Off
IV 1/10V dimming
DX DMX512

CCT OPTIONS


2700K Warm white
3000K Warm white
4000K Neutral white
5000K Cool white
6000K Cool white
RGB
RGBW

COD.	POWER	LED Q.ty	LUMEN	L.COLOUR	B.ANGLE	HOLE (mm)	SIZE (mm)
41181010	10W	48pcs	750 lm	single	30°/60°/120°	1000x22	1000 x 50 x 24 h
41181005	5W	24pcs	375 lm	single	30°/60°/120°	500x22	500 x 50 x 24 h
41182010	10W	48pcs	450 lm	RGB	30°/60°/120°	1000x22	1000 x 50 x 24 h
41182005	5W	24pcs	225 lm	RGB	30°/60°/120°	500x22	500 x 50 x 24 h


OPTIONAL

FINISHING: Silver

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Irina ridefinisce l'eleganza compatta con la luce lineare da incasso più sottile che non scende a compromessi su resistenza e performance. Progettata per resistere alle condizioni climatiche più estreme, umidità e carichi pesanti, è la soluzione perfetta per un'illuminazione outdoor durevole. Il modulo con angolo di fascio regolabile garantisce effetti di lavaggio delle pareti precisi, creando un'atmosfera raffinata in ogni utilizzo. Alimentata dalla tecnologia LED avanzata, unisce efficienza e design ecologico, offrendo una soluzione duratura e ad alte prestazioni per spazi moderni.

Alloggiamento: Alluminio pressofuso con copertura in acciaio inossidabile #6063

Diffusore: Vetro temperato trasparente

Accessori: Scatola in PVC per un'installazione sicura e semplice a terra

LED: LED ad alta efficienza energetica con L80/B10/F10 e una durata di 50.000 ore, che funziona perfettamente a temperature da -21°C a 56°C.

Irina redefines compact elegance with the slimest in-ground linear light that doesn't compromise on strength or performance. Built to withstand the toughest weather conditions, humidity, and heavy loads, it's the ultimate solution for durable outdoor lighting. The adjustable beam angle module ensures precise wall-washing effects, creating a refined ambiance with every use. Powered by advanced LED technology, it combines efficiency with an eco-friendly design, offering a long-lasting and high-performance solution for modern spaces.

Housing: Die-cast aluminum with a sleek stainless steel #6063 cover

Diffuser: Transparent tempered glass

Accessories: PVC box for secure and simple ground installation.

LED: Energy-efficient LED with L80/B10/F10 and a 50,000-hour lifespan, performing flawlessly in temperatures ranging from -21°C to 56°C.

Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

