


LEVIA



VOLTAGE

AC220-240V

DRIVER OPTIONS

OF On/Off
DL DALI
IV 1/10V dimming

CCT OPTIONS

2700K Warm white
3000K Warm white
4000K Neutral white
5000K Cool white

COD.	POWER	LUMEN	B.ANGLE	SIZE (mm)
41324011	11W	570 lm	Asymmetric	Ø200 × 1000 h


OPTIONAL

FINISHING: Black

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Levia vanta un design elegante e moderno, che porta pura bellezza in ogni ambiente. Con la sua luce uniforme, piacevole e soffusa, questo apparecchio crea un'atmosfera più confortevole e stilosa. La tecnologia LED avanzata garantisce una resa luminosa ottimale, riducendo il consumo energetico. Perfetto per applicazioni in giardini, parchi, piccole piazze e viali.

Alloggiamento: realizzato in alluminio pressofuso, verniciato a polvere con una scelta di colori RAL, che offre sia durabilità che una finitura sofisticata per l'uso esterno.

Diffusore: diffusore in PMMA policarbonato, progettato appositamente per LED, che assicura una distribuzione uniforme della luce e un'illuminazione morbida e ambientale.

LED: la tecnologia LED ad alta efficienza riduce il consumo energetico (L80/B10/F10) e vanta una durata di 50.000 ore, con prestazioni affidabili in un intervallo di temperature da -21°C a 56°C.

Levia boasts a sleek and modern design, bringing pure beauty to any space. With its uniform, pleasant, and soft light output, this luminaire creates a more comfortable and stylish environment. The advanced LED technology ensures optimal lumen output while reducing energy consumption. Perfect for a variety of applications, including gardens, parks, small squares, and walkways.

Housing: crafted from die-cast aluminum, powder-coated with a choice of RAL colors, providing both durability and a sophisticated finish for outdoor use.

Diffuser: PMMA polycarbonate diffuser, specially designed for LED, ensuring uniform light distribution and a soft, ambient glow.

LED: energy-efficient LED technology reduces consumption (L80/B10/F10) and boasts a 50,000-hour lifespan, with reliable performance in temperatures ranging from -21°C to 56°C.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

