
LIVIA CS S

LED · COB · CRI >90 · Adjustable · IP44 · AntiDazzle · AntiGlare · 50.000 · Green Production · UGR <19 · SDCM <3 · Sustainable Efficiency · +56° -21° · GWIT 850°





SURFACE / SUPERFICIE

DRIVER OPTIONS

OF On/Off

CCT OPTIONS

2700K	Warm white
3000K	Warm white
4000K	Neutral white
5000K	Cool white
6000K	Cool white
6500K	Cool white

OPTIONAL

FINISHING: White, Black, Brass, Wood
BAFFLE FINISHING: White, Black

COD.	POWER	LUMEN	B.ANGLE	DIM./SIZE (mm)
40120009	9W	550 lm	36°	Ø60 x 57 h

BEAM ANGLE



LIGHT DISTRIBUTION

h(m)	E(lx)	ø(m)
1	1212	ø0.68
2	303.0	ø1.37
3	134.7	ø2.05
4	75.76	ø2.73
5	48.49	ø3.42

COMPLIANCE

LM-79 · TM-21 · LM-80

CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES

A++ · CE · COMPLIANCE · UK CA · CIDET · UL · CCC · ENERGY STAR · EAC · SELV · ROHS · cULus

Livia Cs è un faretto con montaggio a superficie presenta un driver on/off integrato, che offre una rotazione di 355 gradi e un'inclinazione di 45 gradi per un'illuminazione personalizzabile. Il suo design flessibile consente un controllo preciso della direzione della luce, e sono disponibili diverse opzioni di finitura su richiesta per soddisfare le tue esigenze.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Riduce il consumo energetico con una valutazione L80/B10/F10, garantendo una durata di 50.000 ore e prestazioni affidabili in un intervallo di temperature da -21°C a 56°C.

Livia Cs is a surface-mounted spotlight with a built-in on/off driver, offering a 355-degree rotation and 45-degree tilt for customizable illumination. Its flexible design allows for precise control over the lighting direction, and various finishing options are available upon request to suit your needs.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Reduces energy consumption with an L80/B10/F10 rating, providing a 50,000-hour lifespan and reliable performance in temperatures ranging from -21°C to 56°C.

Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at **www.flussirari.it.** These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.