



LUCE TECH S



SURFACE / SUPERFICIE

DRIVER OPTIONS

OF On/Off
PH Phase dimming

CCT OPTIONS


2700K Warm white
3000K Warm white
4000K Neutral white
5000K Cool white
6000K Cool white
6500K Cool white

OPTIONAL

FINISHING: White, Black

COD.	POWER	LUMEN	B. ANGLE	DIM./SIZE (mm)
40131012	12W	1100 lm	15°/24°/36°/60°	Ø80 x 260 x 150 h

BEAM ANGLE



LIGHT DISTRIBUTION

h(m)	E(lx)	Ø(m)
1	2862	Ø0.56
2	715.6	Ø1.12
3	318.0	Ø1.68
4	178.9	Ø2.24
5	114.5	Ø2.79

COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



IT Luce Tech S è un elegante faretto con montaggio a superficie, progettato per installazioni versatili su pareti e soffitti. Il suo design moderno garantisce un'integrazione senza soluzione di continuità in vari ambienti, offrendo un'illuminazione efficace e mirata.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Riduce il consumo energetico con una valutazione L80/B10/F10, garantendo una durata di 50.000 ore e prestazioni affidabili in un intervallo di temperature da -21°C a 56°C.

UK Luce Tech S is a stylish surface-mounted spotlight, designed for versatile installations on both walls and ceilings. Its modern design ensures it seamlessly integrates into various spaces while providing effective and focused lighting.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Reduces energy consumption with an L80/B10/F10 rating, offering a 50,000-hour lifespan and reliable performance in temperatures ranging from -21°C to 56°C.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

