


LUNIA



SURFACE / SUPERFICIE

DRIVER OPTIONS	CCT OPTIONS
OF On/Off	CCT CCT Changeable
DL DALI	
TR Triac	

COD.	POWER	LUMEN	B.ANGLE	SIZE (mm)
40230012	12W	1350 lm	120°	Ø200 x 46 h
40230018	18W	1950 lm	120°	Ø275 x 48 h
40230025	25W	2700 lm	120°	Ø350 x 48 h

OPTIONAL


FINISHING: White

FUNCTION: Motion sensor
Adjustable power

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Italy Lunia è una lampada da soffitto o parete dal design lineare. La sorgente di luce è un LED altamente efficiente che emana luce diretta, pura ed omogenea. Il diffusore si prende cura anche dell'effetto abbagliamento, quindi la luce non disturba l'occhio umano. È perfetto per l'illuminazione di ambienti; la luce è pura e confortevole. Sul retro è presente un interruttore CCT per scegliere la temperatura di colore desiderata (3000K+4000K+5700K).

Alloggiamento: Polycarbonato

Diffusore: Polycarbonato

LED: risparmio energetico L80/B10/F10 - durata 50.000h - temperatura di lavoro da -21°C a 56°

UK Lunia is a surface or wall mounted lamp with linear design. Light source is a high efficiency LED which provides a direct, pure and homogeneous lighting. The diffuser takes care also about the glare effect, so the light does not disturb the human eye. It's perfect for ambient lighting; the light is pure and comfortable. On the back there is a CCT switch to choose the desired color temperature (3000K + 4000K + 5700K).

Housing: Polycarbonate

Diffuser: Polycarbonate

LED: reduce energy consumption with L80/B10/F10 - 50.000 hrs lifetime working under temp (-21°C to 56°C)

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

