
MAGICA

LED · COB · CRI >90 · Fixed · IP44 · AntiDazzle · AntiGlare · 50.000 · Green Production · UGR <19 · SDCM <3 · Sustainable Efficiency · +56° -21° · GWIT 850°







DRIVER OPTIONS

OF On/Off

CCT OPTIONS


2700K	Warm white
3000K	Warm white
4000K	Neutral white
5000K	Cool white
6000K	Cool white
6500K	Cool white

OPTIONAL


FINISHING: White, Black
ACCESSORIES: Lampshield

COD.	POWER	LUMEN	B.ANGLE	DIM./SIZE (mm)
41782035	35 W	2950 lm	24°/38°/60°	Ø80 x 170 h

BEAM ANGLE



LIGHT DISTRIBUTION



h(m)	E(lx)	ø(m)
1	9251	ø0.42
2	2313	ø0.85
3	1028	ø1.27
4	578.2	ø1.70
5	370.0	ø2.12

COMPLIANCE

LM-79 · TM-21 · LM-80

CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES

A++ · CE · COMPLIANCE · UK CA · CIDET · UL · CCC · ENERGY STAR · EAC · SELV · ROHS · cULus

Magica tracklight è composta da un faretto tubolare ultra-slim con adattatore per binario che combina una schermatura a basso abbagliamento con una potenza di 35 watt, offrendo una soluzione di illuminazione elegante ed efficiente. Perfetto per un'illuminazione mirata, il suo design compatto e le caratteristiche ad alte prestazioni garantiscono precisione e comfort. Disponibile anche nella versione sospesa senza binario.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Basso consumo energetico con classificazione L80/B10/F10, garantendo una durata di 50.000 ore. Adatto per temperature comprese tra -21°C e 56°C.

Magica is a track lights, an ultra-slim tubular spot with a track mount adaptor that combines a low-glare shield and a powerful 35-watt output, offering a stylish and efficient lighting solution. Perfect for focused illumination, its compact design and high-performance features ensure precision and comfort. Also available in the suspended version without the track

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Low energy consumption with L80/B10/F10 rating, providing a 50,000-hour lifespan. Suitable for operating temperatures ranging from -21°C to 56°C.

Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at **www.flussirari.it.** These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.