


MAGNETO TL2



DRIVER OPTIONS

OF On/Off
DL DALI
IV 1/10V dimming
TR Triac

CCT OPTIONS


2700K Warm white
3000K Warm white
4000K Neutral white
5000K Cool white
6000K Cool white

COD.	POWER	LUMEN	B.ANGLE	CURRENT	SIZE (mm)
41767006	6W	360 lm	24°/36°	DC48V	113 x 22 x 44 h
41767012	12W	800 lm	24°/36°	DC48V	226 x 22 x 44 h
41767018	18W	1170 lm	24°/36°	DC48V	324 x 22 x 44 h
41767024	24W	1700 lm	24°/36°	DC48V	432 x 22 x 44 h


OPTIONAL

FINISHING: White
Black

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Italy Magneto TL2, un membro della famiglia MAGNETO, è una luce per binario magnetico progettata per un controllo dinamico e flessibile dell'illuminazione. Il suo design unico la rende perfetta per creare effetti di illuminazione personalizzati che valorizzano l'atmosfera e la funzionalità di qualsiasi ambiente.

Alloggiamento: Realizzato in alluminio pressofuso

Riflettore: Riflettore in alluminio anodizzato

Diffusore: Diffusore in vetro trasparente o PMMA

LED: Tecnologia LED all'avanguardia con una valutazione L80/B10/F10, che offre una durata di 50.000 ore. Progettata per operare senza problemi a temperature comprese tra -21°C e 56°C, garantendo risparmi energetici a lungo termine e prestazioni costanti.

UK Magneto TL2, a member of the MAGNETO family, is a magnetic track light designed for flexible and dynamic lighting control. Its unique design makes it perfect for creating tailored lighting effects that enhance the ambience and functionality of any space.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

Diffuser: Transparent glass or PMMA

LED: Cutting-edge LED technology with an L80/B10/F10 rating, providing an impressive 50,000-hour lifespan. Designed to operate flawlessly in extreme temperatures from -21°C to 56°C, offering long-term energy savings and sustained performance.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

