



MICRO



DRIVER OPTIONS

OF On/Off
DL DALI
IV 1/10V dimming
TR Triac

CCT OPTIONS


2700K Warm white
3000K Warm white
4000K Neutral white
5000K Cool white
6000K Cool white
6500K Cool white

OPTIONAL


FINISHING: white

COD.	POWER	LUMEN	B.ANGLE	DIM./SIZE (mm)
40123408	8W	588 lm	15°/24°/36°	Ø50 x 93 h

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Micro è un faretto architettonico a incasso rotondo fisso, progettato con un design semplice. Dotato di un motore di piccole dimensioni e un dissipatore di calore ad alta tecnologia, questo faretto offre uno spettro di luce illimitato. Più luminoso, più sottile, più flessibile e fornisce una maggiore libertà di scelta per i progettisti.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Riduce il consumo energetico con una valutazione L80/B10/F10, garantendo una durata di 50.000 ore e prestazioni affidabili in un intervallo di temperature da -21°C a 56°C.

Micro is an architectural recessed round fixed spotlight, designed with simplicity in mind. Featuring a small-size engine and a high-tech heatsink, this spotlight delivers an unlimited spectrum of light. Offering greater brightness, subtlety, flexibility and it provides designers with enhanced freedom of choice.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Reduces energy consumption with an L80/B10/F10 rating, offering a 50,000-hour lifespan and reliable performance in temperatures ranging from -21°C to 56°C.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

