


NANI



DRIVER OPTIONS	CCT OPTIONS
OF On/Off	2700K Warm white 3000K Warm white 4000K Neutral white 5000K Cool white 6000K Cool white 6500K Cool white
OPTIONAL	

FINISHING: White, Black

COD.	POWER	LUMEN	B. ANGLE	DIM./SIZE (mm)
41781036	36 W	3500 lm	45° x 75°	353 x 52 x 70 h

BEAM ANGLE



🇮🇹 Nani è un wall washer con angolo di fascio di 45° x 75°, progettato per il montaggio su binario trifase e dotato di un'alimentazione integrata on/off. Ideale per creare una diffusione uniforme della luce, il suo design compatto e le caratteristiche ad alte prestazioni garantiscono sia stile che funzionalità.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Basso consumo energetico con classificazione L80/B10/F10, garantendo una durata di 50.000 ore. Adatto per temperature comprese tra -21°C e 56°C.

🇬🇧 Nani wall washer features a 45° x 75° beam angle, designed for 3-phase track mounting and equipped with a built-in on/off power supply. Ideal for creating an efficient and uniform wash of light, its compact design and high-performance features ensure both style and functionality.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Low energy consumption with L80/B10/F10 rating, providing a lifespan of 50,000 hours. Suitable for operating temperatures ranging from -21°C to 56°C.

LIGHT DISTRIBUTION

h(m)	E(lx)	Ø(m)
1	4412	Ø0.79
2	1103	Ø1.59
3	490.3	Ø2.39
4	275.8	Ø3.19
5	176.5	Ø3.99

COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

