




NOVA THERM



DRIVER OPTIONS

OF On/Off
DL DALI

CCT OPTIONS


2200K Warm white
2700K Warm white
3000K Warm white
3500K Warm white
4000K Neutral white
5300K Cool white

COD.	POWER	LUMEN	UNIT CUT	CCT	B. ANGLE	DIM./SIZE (mm)
42758006	6 W/mt	420lm/mt	55.56mm	Single color	120°	1000 x 17 x 16 h

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



La striplight Nova Therm è progettata per resistere ai raggi UV e agli agenti chimici. I connettori fai-da-te intuitivi garantiscono un'installazione semplice in ambienti interni ed esterni. Progettata per la massima flessibilità, il design riconnettibile consente rapide modifiche in loco e un'integrazione perfetta. Dotata di selezione cromatica 3-Step MacAdam e luce senza sfarfallio, offre un'illuminazione costante e di alta qualità per tutta la durata del prodotto. Perfetta per l'uso in sauna grazie alla resistenza alle alte temperature.

LED: Ottimizzata per un'elevata efficienza energetica con L80/B10/F10 – 50.000 ore di funzionamento affidabile su un intervallo di temperatura da -25°C a 100°C.

The Nova Therm striplight is engineered to resist UV exposure and chemical agents. Its intuitive DIY connectors ensure easy installation in both indoor and outdoor environments. Designed for flexibility, the reconnectable design allows quick on-site adjustments and seamless integration. Featuring 3-Step MacAdam binning and flicker-free lighting, it provides consistent, high-quality illumination throughout its lifespan. Ideal for sauna applications thanks to its high-temperature resistance.

LED: Optimized for superior energy efficiency with L80/B10/F10 – 50,000 hours of reliable operation across a temperature range of -25°C to 100°C.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

