


OTTICA SR



SURFACE / SUPERFICIE

DRIVER OPTIONS

OF On/Off
TR Triac

CCT OPTIONS

2700K Warm white
3000K Warm white
4000K Neutral white
5000K Cool white
6000K Cool white
6500K Cool white


OPTIONAL

FINISHING: White trim


REFLECTOR: Shining Silver

COD.	HEADS	POWER	LUMEN	B.ANGLE	SIZE (mm)
30200015	1	15W	810 lm	15°/24°/30°/36°/60°	120 x 120 x 175 h
30200020	1	20W	1080 lm	15°/24°/30°/36°/60°	120 x 120 x 175 h
30201030	2	2x15W	1620 lm	15°/24°/30°/36°/60°	120 x 230 x 175 h
30201040	2	2x20W	2160 lm	15°/24°/30°/36°/60°	120 x 230 x 175 h

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



🇮🇹 Ottica SR offre diverse versioni che abbracciano l'innovazione con prestazioni eccellenti, unicità, durabilità e versatilità. Con una rotazione orizzontale di 350° e un'inclinazione di 25° da sinistra a destra, permette regolazioni precise dell'angolo per un'illuminazione mirata. Progettata per soddisfare diverse esigenze, questa lampada è perfetta sia per scopi funzionali che estetici.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Tecnologia LED a basso consumo con una classificazione L80/B10/F10, con una durata di 50.000 ore. Funziona in un intervallo di temperatura da -21°C a 56°C, garantendo prestazioni affidabili e durature.

🇬🇧 Ottica SR offers multiple versions that embrace innovation with outstanding performance, uniqueness, durability, and versatility. With 350° horizontal rotation and a 25° tilt from left to right, it allows precise angle adjustments for targeted lighting. Designed to meet various needs, this lamp is perfect for both functional and aesthetic purposes.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Energy-efficient LED technology with an L80/B10/F10 rating, offering a 50,000-hour lifespan. Operates within a temperature range of -21°C to 56°C, ensuring reliable and long-term performance.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

