


PLATINO R



RECESSED / A INCASSO


DRIVER OPTIONS	CCT OPTIONS
OF On/Off	2700K Warm white 3000K Warm white 4000K Neutral white 5000K Cool white 6000K Cool white 6500K Cool white
OPTIONAL	

FINISHING: Stainless Steel

ACCESSORIES: Honeycomb Louvre, Plaster Kit

COD.	POWER	LUMEN	B.ANGLE	HOLE (mm)	DIM./SIZE (mm)
42925010	10W	500 lm	15°/24°/36°	152 x 42	49 x 160 x 46 h

BEAM ANGLE



LIGHT DISTRIBUTION

h(m)	E(lx)	Ø(m)
1	2294	Ø0.42
2	573.6	Ø0.84
3	254.9	Ø1.26
4	143.4	Ø1.68
5	91.78	Ø2.09

COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Platino R è uno spot lineare per doccia, progettato per un'estetica moderna e raffinata, disponibile con una griglia a nido d'ape opzionale per ridurre l'abbagliamento. L'installazione semi-incassata conferisce un aspetto pulito e a filo, ed è possibile un montaggio facile tramite un kit d'intonaco.

Alloggiamento: Alluminio pressofuso, per resistenza e un aspetto raffinato.

Riflettore: Alluminio anodizzato, progettato per ottimizzare la riflessione della luce e l'efficienza.

LED: Tecnologia LED a basso consumo con una classificazione L80/B10/F10, con una durata di 50.000 ore. Funziona in un intervallo di temperatura da -21°C a 56°C, garantendo prestazioni affidabili e durature.

Platino R is a linear shower spot designed for sleek, modern aesthetics, available with an optional honeycomb louvre to reduce glare. Its semi-recessed installation provides a clean, flush appearance, and it can be easily mounted with a plaster kit.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Energy-efficient LED technology with an L80/B10/F10 rating, offering a 50,000-hour lifespan. Operates in temperatures ranging from -21°C to 56°C, ensuring long-term reliability and performance.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

