


PRATO



BEAM ANGLE



Prato è una luce da parete piatta progettata per offrire un'illuminazione versatile con luci sia verso l'alto che verso il basso, ideale per creare effetti luminosi unici negli ambienti contemporanei. Il suo design raffinato arricchisce l'estetica di qualsiasi stanza, offrendo prestazioni efficaci e durature.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Tecnologia LED a basso consumo con una classificazione L80/B10/F10, con una durata di 50.000 ore. Funziona in un intervallo di temperatura da -21°C a 56°C, garantendo prestazioni costanti e durature.

Prato is a flat wall light designed to provide versatile illumination with both up and down lighting features, perfect for creating unique lighting effects in contemporary settings. Its refined design enhances the aesthetic of any room while delivering effective and lasting performance.

Housing: Die-cast aluminum.

Reflector: Anodized aluminum

LED: Energy-efficient LED technology with an L80/B10/F10 rating, offering a 50,000-hour lifespan. Operates within a temperature range of -21°C to 56°C, ensuring consistent and long-lasting performance.

COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

