


RAGNO V1



VOLTAGE

AC100-240V / DC24V

DRIVER OPTIONS

OF On/Off

CCT OPTIONS

2700K Warm white
3000K Warm white
4000K Neutral white
5000K Cool white
6500K Cool white


OPTIONAL

FINISHING: Silver

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



COD.	POWER	LED Q.ty	LUMEN	B.ANGLE	FORO/HOLE (mm)	SIZE (mm)
41180010	10W	1pc	100 lm	1x60°	Ø64	Ø90 x 92 h
41181003	3W	1pc	30 lm	1x60°	Ø64	Ø90 x 92 h

Italy Ragno V1 è la soluzione perfetta per esigenze di illuminazione minimalista, con una singola uscita di luce che offre illuminazione focalizzata per specifici elementi del paesaggio. Realizzato con un corpo in lega di alluminio 6063 e finitura anodizzata, garantisce prestazioni durature, mentre la piastra frontale in acciaio inox ne aumenta la durata. La copertura in vetro temperato ad alta resistenza assicura una distribuzione uniforme e chiara della luce per un effetto di illuminazione raffinato.

Alloggiamento: Alluminio pressofuso con copertura in acciaio inox, disponibile nelle finiture 309 e 316.

Diffusore: Vetro temperato trasparente.

Accessori: Include una scatola in PVC per un'installazione sicura nel terreno.

LED: Tecnologia LED ad alta efficienza con prestazioni L80/B10/F10, durata di 50.000 ore e funzionamento efficace in un intervallo di temperature da -21°C a 56°C

UK Ragno V1 in-ground light is the perfect solution for minimalist lighting needs, with a single light exit that delivers focused illumination for specific landscape features. Constructed with a 6063 aluminium alloy body and anodized finish, it provides long-lasting performance, while the stainless steel faceplate adds durability. The high-strength toughened glass lampshade ensures uniform, clear light distribution for a refined lighting effect.

Housing: Die-cast aluminium with a stainless steel cover, available in 309 and 316 finishes.

Diffuser: Transparent tempered glass.

Accessories: Includes a PVC box for secure ground installation.

LED: High-efficiency LED technology with L80/B10/F10 performance, a 50,000-hour lifespan, and effective operation in temperatures from -21°C to 56°C.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

