


RAGNO V4



VOLTAGE

AC100-240V / DC24V

DRIVER OPTIONS

OF On/Off

CCT OPTIONS

2700K Warm white
3000K Warm white
4000K Neutral white
5000K Cool white
6500K Cool white

COD.	POWER	LED Q.ty	LUMEN	B.ANGLE	FORO/HOLE (mm)	SIZE (mm)
41181008	8W	4pcs	80 lm	4x60°	Ø64	Ø90 x 92 h


OPTIONAL

FINISHING: Silver

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Italy Ragno V4 è una soluzione compatta ma potente con quattro uscite di luce, ideale per mettere in risalto aree esterne più piccole. Il corpo in lega di alluminio 6063 con trattamento anodizzato garantisce una lunga affidabilità, mentre la piastra frontale in acciaio inox aumenta la durata. La copertura in vetro temperato ad alta resistenza fornisce una luce chiara e uniforme, perfetta per creare un'atmosfera calda e accogliente.

Alloggiamento: Alluminio pressofuso con copertura in acciaio inox, disponibile nelle finiture 309 e 316.

Diffusore: Vetro temperato trasparente.

Accessori: Include una scatola in PVC per un'installazione facile a terra.

LED: LED a basso consumo con prestazioni L80/B10/F10, durata di 50.000 ore e funzionamento efficace da -21°C a 56°C.

UK Ragno V4 in-ground light is a compact yet powerful solution featuring four light exits, perfect for accentuating smaller outdoor areas. Its 6063 aluminium alloy body with anodizing treatment ensures long-term reliability, while the stainless steel faceplate provides enhanced durability. The high-strength toughened glass lampshade produces a clear, uniform light, perfect for creating a warm, inviting atmosphere.

Housing: Die-cast aluminium with a stainless steel cover, available in 309 and 316 finishes.

Diffuser: Transparent tempered glass.

Accessories: Comes with a PVC box for easy ground installation.

LED: Energy-efficient LED with L80/B10/F10 performance, 50,000-hour lifespan, and effective operation from -21°C to 56°C.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

