


RASO



RECESSED / A INCASSO

DRIVER OPTIONS

OF On/Off
DL DALI
IV 1/10V dimming
TR Triac
PH Phase dimming

OPTIONAL

CCT OPTIONS

3000K Warm white
4000K Neutral white

FINISHING: White

COD.	POWER	LUMEN	B.ANGLE	HOLE (mm)	SIZE (mm)
40054010	10W	647 lm	Asymmetric	Ø75	Ø85 x 72 h
40054015	15W	982 lm	Asymmetric	Ø75	Ø85 x 72 h
40055015	15W	975 lm	Asymmetric	Ø95	Ø108 x 87 h
40055020	20W	1340 lm	Asymmetric	Ø95	Ø108 x 87 h
40056025	25W	1627 lm	Asymmetric	Ø125	Ø135 x 99 h
40056030	30W	1962 lm	Asymmetric	Ø125	Ø135 x 99 h

BEAM ANGLE



■ Raso è una gamma di faretti architettonici a incasso per illuminazione a parete, progettati per un'installazione a filo contro soffitti falsi. Le versioni minime (senza flap perimetrale) sono compatibili con spessori di soffitto di 12,5 mm, mentre le versioni con telaio (con flap) si adattano a soffitti da 1 a 25 mm, utilizzando molle di torsione per un'installazione sicura. L'ottica innovativa e brevettata per l'illuminazione a parete garantisce una luce uniforme dalla parte più alta alla più bassa della parete, evitando anche zone d'ombra nelle aree vicino al soffitto.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

Diffusore: Lente PMMA

LED: Riduce il consumo energetico con L80/B10/F10, con una durata di 50.000 ore, e funziona in modo efficace tra -20°C e 50°C.

■ Raso is a range of architectural recessed wall washer spotlights, designed for flush-mount installation on false ceilings. The minimal versions (without perimeter flap) are compatible with ceiling thicknesses of 12.5 mm, while frame versions (with flap) can be installed on ceilings ranging from 1 to 25 mm, utilizing torsion springs for secure installation. The innovative, patented wall washer optic ensures uniform lighting from the highest to the lowest points on the wall, while also preventing shadow areas near the ceiling.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

Diffuser: PMMA lens

LED: Reduces energy consumption with L80/B10/F10, offering a 50,000-hour lifespan, and operates effectively between -20°C and 50°

COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

