



RIFLESSI R



RECESSED / A INCASSO

DRIVER OPTIONS	CCT OPTIONS		COD.	POWER	LUMEN	B.ANGLE	HOLE (mm)	DIM./SIZE (mm)
OF On/Off	2700K	Warm white	42920010	10W	720 lm	15°/24°/36°	Ø64	Ø70 x 60 h
	3000K	Warm white						
	4000K	Neutral white						
	5000K	Cool white						
	6000K	Cool white						
	6500K	Cool white						
OPTIONAL								
FINISHING: White, Black								

BEAM ANGLE



LIGHT DISTRIBUTION

h(m)	E(lx)	Ø(m)
1	2118	Ø0.40
2	529.6	Ø0.80
3	235.4	Ø1.20
4	132.4	Ø1.60
5	84.74	Ø2.00

COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



IT Riflessi R è una plafoniera rotonda semi-incassata con un baffo profondamente incassato, progettata per offrire un UGR molto basso, specialmente nella versione con finitura nera. Il suo design moderno ed elegante garantisce una diffusione ottimale della luce e comfort visivo.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Tecnologia LED a basso consumo con una classificazione L80/B10/F10, con una durata di 50.000 ore. Funziona in un intervallo di temperatura da -21°C a 56°C, garantendo prestazioni affidabili nel tempo.

UK Riflessi R is a round semi-recessed light with a deep recessed baffle, designed to offer very low UGR, particularly in the black finish version. Its modern and sleek design ensures optimal light diffusion and visual comfort.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Energy-efficient LED technology with an L80/B10/F10 rating, offering a 50,000-hour lifespan. Operates within a temperature range of -21°C to 56°C, ensuring reliable performance over time.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

