



SPIRA



RECESSED / A INCASSO

DRIVER OPTIONS

OF On/Off

CCT OPTIONS

2700K Warm white
3000K Warm white
4000K Neutral white
5000K Cool white
6000K Cool white
6500K Cool white

OPTIONAL

FINISHING: White, Black

COD.	POWER	LUMEN	B.ANGLE	HOLE (mm)	DIM./SIZE (mm)
40132012	12W	598 lm	24°	206 x 26	218 x 39 x 46 h

BEAM ANGLE



LIGHT DISTRIBUTION

h(m)	E(lx)	ø(m)
1	164.8	ø0.65
2	41.20	ø1.30
3	18.31	ø1.95
4	10.60	ø2.60
5	6.591	ø3.25

COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Spira è un wall washer fisso con un design speciale a lama, disponibile in una versione a cornice sottile, che offre un'estetica elegante e moderna. Fornisce un'illuminazione efficiente per il wall washing, ideale per creare effetti di luce uniformi su superfici verticali.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Riduce il consumo energetico con una valutazione L80/B10/F10, garantendo una durata di 50.000 ore e prestazioni affidabili in un intervallo di temperature da -21°C a 56°C.

Spira is a fixed wall washer featuring a unique blade design in a slim trim version, offering a sleek and modern aesthetic. It provides efficient wall-washing illumination, ideal for creating uniform lighting effects on vertical surfaces.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Reduces energy consumption with an L80/B10/F10 rating, providing a 50,000-hour lifespan and reliable performance in temperatures ranging from -21°C to 56°C.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

