


STELO FL1



VOLTAGE

AC100-240V 50/60HZ

DRIVER OPTIONS

OF On/Off
DL DALI
IV 1/10V dimming
TR Triac

CCT OPTIONS

2700K Warm white
3000K Warm white
4000K Neutral white
6000K Cool white


OPTIONAL

FINISHING: Black




COD.	POWER	LUMEN	B.ANGLE	SIZE (mm)
40901003	3W	109 lm	8°/15°/25°/40°	Ø 75 x 213 h
40902011	11W	708 lm	15°/24°/36°/50°/20°x50°	Ø 75 x 330 h
40905011	11W	708 lm	15°/24°/36°/50°/20°x50°	Ø 75 x 700 l
40903020	20W	1875 lm	15°/24°/36°/50°/20°x50°	Ø 140 x 466 h
40904030	30W	2577 lm	15°/24°/36°/50°/20°x50°	Ø 140 x 588 h
40904040	40W	3629 lm	15°/24°/36°/50°/20°x50°	Ø 140 x 588 h

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Stelo FL1 è realizzato con materiali ad alta resistenza, garantendo protezione contro le intemperie grazie all'alloggiamento in alluminio pressofuso rivestito a polvere, base di montaggio regolabile, picchetto da terra e parasole. Il sistema LED ad alta efficienza assicura alte prestazioni con basso consumo energetico, offrendo un design elegante ed ecologico.

Alloggiamento: Alluminio pressofuso verniciato a polvere.

Riflettore: Lente ottica

Riflettore: Vetro temperato trasparente.

LED: Alta efficienza energetica (L80/B10/F10), durata di 50.000 ore, funzionante da -21°C a 56°C.

Stelo FL1 is built from high-resistance materials, offering weatherproof protection with a powder-coated aluminum housing, adjustable mounting base, ground stake, and glare shield. The light features an efficient LED system, balancing high performance with low energy consumption. This stylish, eco-friendly fixture ensures significant energy savings.

Housing: Powder-coated die-cast aluminum.

Diffuser: Transparent tempered glass.

Reflector: Optical lens

LED: Energy-efficient (L80/B10/F10), 50,000-hour lifespan, operating from -21°C to 56°C.

Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

