


STENOPO



DRIVER OPTIONS	CCT OPTIONS	COD.	POWER	LUMEN	B.ANGLE	HOLE (mm)	DIM./SIZE (mm)
OF On/Off	2700K Warm white 3000K Warm white 4000K Neutral white 5000K Cool white 6000K Cool white 6500K Cool white	41408003	3W	60 lm	Flush	Ø33-35	Ø39 x 33
OPTIONAL							
FINISHING: White, Black							

BEAM ANGLE



Stenopo è una lampada da parete a basso abbagliamento, progettata per un'illuminazione discreta ma efficace. Con una cornice rotonda e un design fluido, combina eleganza e prestazioni ottimali. Il suo stile essenziale arricchisce gli spazi esterni con un tocco sofisticato, offrendo un'illuminazione precisa e priva di abbagliamento. Progettato per durare nel tempo, Stenopo garantisce prestazioni eccellenti in qualsiasi ambiente, rendendolo una soluzione affidabile per l'illuminazione esterna moderna.

Alloggiamento: Alluminio pressofuso

Riflettore: Alluminio anodizzato

LED: Tecnologia LED a basso consumo con classificazione L80/B10/F10, durata di 50.000 ore e prestazioni costanti con temperature da -21°C a 56°C

Stenopo is a low-glare wall light designed for subtle yet effective illumination. With its round bezel and seamless circular form, it offers a refined balance of elegance and performance. Its minimalist design enhances outdoor spaces with a sophisticated touch, delivering precise, glare-free lighting. Engineered for longevity, Stenopo maintains exceptional performance in all environments, making it a dependable choice for modern exterior lighting.

Housing: Die-cast aluminum

Reflector: Anodized aluminum

LED: Energy-efficient LED with an L80/B10/F10 rating, delivering 50,000 hours of consistent illumination across temperatures from -21°C to 56°C

COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

