


TERAL OPAL



VOLTAGE

AC100-240V

DRIVER OPTIONS

OF On/Off
DL DALI
TR Triac
DX DMX512

CCT OPTIONS

2700K Warm white
3000K Warm white
4000K Neutral white
6000K Cool white
RGB

COD.	POWER	LUMEN	B.ANGLE	HOLE (mm)	SIZE (mm)
41104003	3W	25 lm	100°	Ø 93	Ø 100 x 130 h
41106006	6W	47 lm	100°	Ø 119	Ø 130 x 145 h
41109008	8W	80 lm	100°	Ø 145	Ø 160 x 155 h


OPTIONAL

FINISHING: Silver

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Italy Teral Opal è progettato per offrire una luce soffusa e ambientale che arricchisce ogni ambiente esterno. Con il suo diffusore in vetro opale, questo faretto crea una luce calda e diffusa, perfetta per l'illuminazione generale delle aree. Il robusto alloggiamento in alluminio pressofuso garantisce una durata eccezionale, mentre la tecnologia LED ad alta efficienza offre prestazioni che risparmiano energia senza compromettere la luminosità. Perfetto per percorsi, giardini o caratteristiche del paesaggio, il Teral Opal unisce affidabilità ed eleganza in una sola soluzione.

Alloggiamento: Alluminio pressofuso con copertura in acciaio inossidabile

Diffusore: Vetro opale

LED: Tecnologia LED ad alta efficienza (L80/B10/F10), con una durata di 50.000 ore e prestazioni ottimali a temperature da -21°C a 56°C

UK Teral Opal is designed to provide a soft, ambient glow that enhances any outdoor environment. With its frosted glass diffuser, this luminaire creates a warm and diffused light, perfect for general area illumination. The robust die-cast aluminum housing ensures long-lasting durability, while the high-efficiency LED technology delivers energy-saving performance without sacrificing brightness. Ideal for outdoor pathways, gardens, or landscape features, the Teral Opal offers reliability and elegance in one package.

Housing: Die-cast aluminum body with stainless steel cover

Diffuser: Frosted glass

LED: Energy-efficient LED technology (L80/B10/F10), offering a 50,000-hour lifespan and optimal performance in temperatures from -21°C to 56°C

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

