


VIA



VOLTAGE

AC220-240V



DRIVER OPTIONS

OF On/Off
DL DALI
IV 1/10V dimming

CCT OPTIONS

2700K Warm white
3000K Warm white
4000K Neutral white
5000K Cool white

COD.	POWER	LUMEN	B.ANGLE	SIZE (mm)
41325011	11W	450 lm	Asymmetric	120 x 120 x 500 h
41326011	11W	450 lm	Asymmetric	120 x 120 x 800 h


OPTIONAL

FINISHING: Black

BEAM ANGLE



LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



Italia Via presenta un design moderno e raffinato, disponibile in due dimensioni, che unisce bellezza e funzionalità. La sua luce pulita, uniforme e calda crea un'atmosfera elegante e accogliente, rendendo ogni spazio più confortevole. La tecnologia LED avanzata garantisce una resa luminosa ottimale e un notevole risparmio energetico. Ideale per molteplici applicazioni, come giardini, parchi, piccole piazze o viali.

Alloggiamento: realizzato in alluminio pressofuso, verniciato a polvere con una selezione di colori RAL, che offre durabilità e una finitura elegante per ambienti esterni.

Diffusore: diffusore in PMMA policarbonato, progettato appositamente per LED, che garantisce una distribuzione uniforme della luce e un'illuminazione morbida e ambientale.

LED: la tecnologia LED ad alta efficienza riduce il consumo energetico (L80/B10/F10) e offre una durata impressionante di 50.000 ore, con prestazioni affidabili in temperature comprese tra -21°C e 56°C.

UK Via features a sleek and modern design in two sizes, blending beauty with functionality. Its clean, uniform, and warm light output creates a stylish and inviting atmosphere, making any space feel more comfortable. The advanced LED technology ensures optimal lumen performance and significant energy savings. Ideal for a wide range of applications, including gardens, parks, small squares, or pathways.

Housing: crafted from die-cast aluminum, powder-coated with a selection of RAL colors, offering both durability and an elegant finish for outdoor environments.

Diffuser: PMMA polycarbonate diffuser, specially designed for LED, providing even light distribution and a soft, ambient glow.

LED: energy-efficient LED technology reduces consumption (L80/B10/F10) and provides an impressive 50,000-hour lifespan, with reliable performance in temperatures ranging from -21°C to 56°C.

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

