


VIAGGIO



DRIVER OPTIONS

OF On/Off
DX DMX512

CCT OPTIONS


2700K Warm white
3000K Warm white
4000K Neutral white
6000K Cool white
RGB

COD.	POWER	LUMEN	B.ANGLE	HOLE (mm)	SIZE (mm)
41145005	4.5W	48 lm	120°	262 x 42	260 x 40 x 130 h
41145008	8W	86 lm	120°	592 x 42	590 x 40 x 130 h
41145015	15W	230 lm	120°	1002 x 42	1000 x 40 x 130 h


OPTIONAL

FINISHING: Black

BEAM ANGLE




Continuous connection



Right angle connector

LIGHT DISTRIBUTION



COMPLIANCE



CERTIFICATIONS / POWER SUPPLY COMPLIANCE CHOICES



■ Lampada a incasso terra. Per creare effetti luminosi lineari senza punti in ombra, il tutto con la robustezza e la resistenza al carico di una lampada da terra.

Alloggiamento: alluminio pressofuso

Diffusore: vetro temperato

LED: risparmio energetico L80/B10/F10 - durata 50.000 h - temperature di lavoro da -21°C a 56°

🇬🇧 Recessed floor lamp. To create linear lighting effects without shadow spots, all with the robustness and load resistance of a floor lamp.

Housing: die casting aluminium

Diffuser: tempered glass

LED: reduce energy consumption with L80/B10/F10 - 50.000 hrs lifetime working under temp (-21°C to 56°C)

! Beam angles, optics tailored for specific projects, asymmetric effects, special lenses, opal diffusers, reflector RAL color (if different from white), and the use of anti-glare accessories collectively contribute to variations in total lumen flux compared to the technical sheet data.

Flussirari reserves the right to modify the characteristics of its products and their availability without prior notice. The information provided, including product details, technical data, illustrations, and specifications, is not considered binding. Flussirari accepts no liability for any discrepancies. In our continuous pursuit of product enhancement, we retain the prerogative to make changes to specifications or materials without prior notification, provided such modifications do not compromise the functionality of the product.

For the most current and authoritative specifications, users are advised to refer to the specification sheets available at www.flussirari.it. These documents supersede all other printed or electronic versions and are reflective of the latest updates and revisions.

Compliance may vary in each power supply based on country-specific technical regulations.

